

10 Pin 16A 500V Heavy Duty Connector Male Insert

These are related to the 10 Pin 16A 500V Heavy Duty Connector Male Insert information, in which you can learn about the updated information in 10 Pin 16A 500V Heavy Duty Connector Male Insert, to help you better understand and expand 10 Pin 16A 500V Heavy Duty Connector Male Insert market. Because the market for 10 Pin 16A 500V Heavy Duty Connector Male Insert is evolving and changing,



Product Description

The following is the introduction of high quality 10 Pin 16A 500V Heavy Duty Connector Male Insert , hoping to help you better understand 10 Pin 16A 500V Heavy Duty Connector Male Insert. Manufacturer Supplied Heavy Duty Connector with CE and UL Approval Compliant with All Harting Category Range Welcome new and old customers to continue working with us to create a better future!

Product Description

10 Pin 16A 500V Heavy Duty Connector Male Insert is a Heavy Duty Connector manufacturer with TUV audit.We also have CE,UL,EAC certified high performance connectors. ISO quality management system. Patent configuration, easy installation, quick installation. Personalized interfaces for different scenarios. High quality raw material guarantee. Create more environmentally friendly products.

Basic Info.

Model NO.	HZW-HE-010M
Contacts Surface Treatment	Silver/Glod Plated
Housing Material	Die-Casting Aluminum Alloy
Working Environments	IP65 for Various Harsh Environments
Contact Cost	Pay Additional Cost for Crimp Contacts
Specification	CE, UL, ROHS



Origin	China
Production Capacity	3000pieces Per Day
Certification	UL
Contact Material	Copper
Housing Coating	Anti-Corrosion Powder Spray
Crimp Tooling	Available
Transport Package	Poly bag and Double Cartons
Trademark	Oukerui
HS Code	8536900000

SPECIFICATION

Model No.	HZW-HE-010M
Terminal type	Screw Terminal
Housings material	Dia casting aluminum alloy
Working Voltage	500V
Rated Impulse Voltage	6KV
International protection(IP) grade	IP65
Flammability	V0
Mechanical Life Span	Min 500 times
Warranty	1 Year
Gender type	Male
Contacts' surface processing	Silver or Gold Plated
Mounting type	Bulkhead/Surface/ cable to cable
Insert Block	Top grade PC
Working Current	16A
Temperature Bearing Range	-40° C~+125° C
Pollution Degree	3
Transport packing	Carton



SPECIFICATION OF CONTACT

Material	Copper Alloy
Terminal	Screw/Crimp Terminal
Screw terminal tightening	0.5Nm
Surface Treatment	Silver/Gold Plated
Wire Gauge	1.0-2.5mm ² (AWG18-14)
Stripping length	7-9mm

10 Pin 16A 500V Heavy Duty Connector Male Insert are extensively used in equipment that require electrical and signal connections, such as mold, machinery, construction machinery, textile machinery, transportation technology, electric energy, electric locomotives and so on various need electrical and petrochemical equipment.